

Quit

The *Quit* action quits *OpenOffice/LibreOffice Base*. You can select one of several options for saving the database document before quitting.

tags:
[Actions](#)

Applies to ...

Object	Description
DoCmd	Root class. When present, its name must be " DoCmd " but the object name is optional.

Syntax

[DoCmd.]Quit(*Option*)

Argument	Optional	Type or Symbol	Description
<i>Option</i>	Yes	acQuitPrompt, acQuitSaveAll, acQuitSaveNone	<i>acQuitPrompt</i> Displays a dialog box that asks whether you want really to quit or not. <i>acQuitSaveAll</i> (default) Saves all objects without displaying a dialog box. <i>acQuitSaveNone</i> Quits without saving any objects.

The symbolic constants can be included in your code by copying and pasting next lines:

```
Const acQuitPrompt = 0
Const acQuitSaveAll = 1
Const acQuitSaveNone = 2
```

Remarks

- The Quit action has the same effect as clicking Exit on the File menu in the *OpenOffice/LibreOffice Base* window.
- In *MSAccess* the *Quit* method is linked to the **Application** object.
- The *Quit* action must not be triggered from a **standalone form**.

Error messages

Action not applicable in this context

See also

Example

Display next message box: **Do you really want to quit the application ? Changed data will be saved.**
 If Yes pressed, the application will close.

```
DoCmd.Quit(acQuitPrompt)
```

Bookmark this page » » [Quit](#)